

Package ‘shinylogs’

July 23, 2025

Title Record Everything that Happens in a 'Shiny' Application

Version 0.2.1

Description Track and record the use of applications and the user's interactions with 'Shiny' inputs. Allows to trace the inputs with which the user interacts, the outputs generated, as well as the errors displayed in the interface.

License GPL-3

Encoding UTF-8

RoxygenNote 7.1.2

URL <https://github.com/dreamRs/shinylogs>

BugReports <https://github.com/dreamRs/shinylogs/issues>

Imports htmltools, shiny (>= 1.1.0), jsonlite, data.table, bit64, nanotime, digest, anytime

Suggests testthat, knitr, rmarkdown, covr, DBI, RSQLite, googledrive

VignetteBuilder knitr

NeedsCompilation no

Author Fanny Meyer [aut],
Victor Perrier [aut, cre],
Silex Technologies [fnd] (<https://www.silex-ip.com>)

Maintainer Victor Perrier <victor.perrier@dreamrs.fr>

Repository CRAN

Date/Publication 2022-04-18 16:20:02 UTC

Contents

read_json_logs	2
read_rds_logs	3
store_custom	3
store_googledrive	5
store_json	6
store_null	8

store_rds	9
store_sqlite	11
track_usage	13
use_tracking	17

Index	20
--------------	-----------

read_json_logs	<i>Read a directory containing JSON logs</i>
----------------	--

Description

Read a directory containing JSON logs

Usage

```
read_json_logs(path)
```

Arguments

path Path of the directory containing JSON files or a vector of path to JSON files.

Value

a list of data.table

Examples

```
# Read all JSON in a directory
path_directory <- system.file("extdata/json", package = "shinylogs")
logs <- read_json_logs(path = path_directory)

# Read a single file
single_file <- dir(
  path = system.file("extdata/json", package = "shinylogs"),
  full.names = TRUE
)[1]
logs <- read_json_logs(path = single_file)
```

read_rds_logs	<i>Read a directory containing RDS logs</i>
---------------	---

Description

Read a directory containing RDS logs

Usage

```
read_rds_logs(path)
```

Arguments

path Path of the directory containing RDS files or a vector of path to RDS files.

Value

a list of data.table

Examples

```
## Not run:  
# Read all RDS in a directory  
logs <- read_rds_logs(path = "path/to/directory")  
  
# Read a single file  
logs <- read_rds_logs(path = "path/to/log.rds")  
  
## End(Not run)
```

store_custom	<i>Use custom function to save logs</i>
--------------	---

Description

Store logs tracked where you want by providing a custom function to write them in your preferred location.

Usage

```
store_custom(FUN, ...)
```

Arguments

FUN A function that take at least one argument logs, that will correspond to logs recorded as a list.
... Extra parameters that will be passed to FUN.

Value

A list that can be used in `track_usage()`.

Examples

```
library(shiny)
library(shinylogs)

# Classic Iris clustering with Shiny
ui <- fluidPage(

  headerPanel("Iris k-means clustering"),

  sidebarLayout(
    sidebarPanel(
      selectInput(
        inputId = "xcol",
        label = "X Variable",
        choices = names(iris)
      ),
      selectInput(
        inputId = "ycol",
        label = "Y Variable",
        choices = names(iris),
        selected = names(iris)[[2]]
      ),
      numericInput(
        inputId = "clusters",
        label = "Cluster count",
        value = 3,
        min = 1,
        max = 9
      )
    ),
    mainPanel(
      plotOutput("plot1")
    )
  )
)

server <- function(input, output, session) {

  # Just take a look at what is generated
  track_usage(
    storage_mode = store_custom(FUN = function(logs) {
      str(logs, max.level = 3)
      invisible()
    })
  )

  # classic server logic
```

```
selectedData <- reactive({
  iris[, c(input$xcol, input$ycol)]
})

clusters <- reactive({
  kmeans(selectedData(), input$clusters)
})

output$plot1 <- renderPlot({
  palette(c("#E41A1C", "#377EB8", "#4DAF4A", "#984EA3",
           "#FF7F00", "#FFFF33", "#A65628", "#F781BF", "#999999"))

  par(mar = c(5.1, 4.1, 0, 1))
  plot(selectedData(),
        col = clusters()$cluster,
        pch = 20, cex = 3)
  points(clusters()$centers, pch = 4, cex = 4, lwd = 4)
})

}

if (interactive())
  shinyApp(ui, server)
```

store_googledrive *Use Google Drive as storage mode*

Description

All logs will be written in the same file.

Usage

```
store_googledrive(path)
```

Arguments

path Path to folder on Drive where to send logs.

Value

A list that can be used in [track_usage\(\)](#).

Note

See the gargle package to manage authentication, and especially [this vignette from gargle package](#) to manage the process.

Examples

```
## Not run:
# In your global, manage Google Drive access
drive_auth(path = "/path/to/your/service-account-token.json")
# see https://gargle.r-lib.org/articles/articles/managing-tokens-securely.html
# to manage your token securely

# Then in server, use:
track_usage(storage_mode = storegoogledrive(path = "my-logs/"))

# you may have to share my-logs/ folder with your service account

## End(Not run)
```

store_json

Use JSON files as storage mode

Description

One JSON will be written for each session of the application.

Usage

```
store_json(path)
```

Arguments

path Path where to write JSON files.

Value

A list that can be used in [track_usage\(\)](#).

Examples

```
library(shiny)
library(shinylogs)

# temp directory for writing logs
tmp <- tempdir()

# when app stop,
# navigate to the directory containing logs
onStop(function() {
  browseURL(url = tmp)
})

# Classic Iris clustering with Shiny
```

```
ui <- fluidPage(  
  headerPanel("Iris k-means clustering"),  
  
  sidebarLayout(  
    sidebarPanel(  
      selectInput(  
        inputId = "xcol",  
        label = "X Variable",  
        choices = names(iris)  
      ),  
      selectInput(  
        inputId = "ycol",  
        label = "Y Variable",  
        choices = names(iris),  
        selected = names(iris)[[2]]  
      ),  
      numericInput(  
        inputId = "clusters",  
        label = "Cluster count",  
        value = 3,  
        min = 1,  
        max = 9  
      )  
    ),  
    mainPanel(  
      plotOutput("plot1")  
    )  
  )  
)  
  
server <- function(input, output, session) {  
  
  # Store JSON with logs in the temp dir  
  track_usage(  
    storage_mode = store_json(path = tmp)  
  )  
  
  # classic server logic  
  
  selectedData <- reactive({  
    iris[, c(input$xcol, input$ycol)]  
  })  
  
  clusters <- reactive({  
    kmeans(selectedData(), input$clusters)  
  })  
  
  output$plot1 <- renderPlot({  
    palette(c("#E41A1C", "#377EB8", "#4DAF4A", "#984EA3",  
             "#FF7F00", "#FFFF33", "#A65628", "#F781BF", "#999999"))  
  
    par(mar = c(5.1, 4.1, 0, 1))  
  })  
}
```

```
    plot(selectedData(),
          col = clusters()$cluster,
          pch = 20, cex = 3)
    points(clusters()$centers, pch = 4, cex = 4, lwd = 4)
  })
}

if (interactive())
  shinyApp(ui, server)
```

store_null

No storage on disk

Description

Doesn't write anything, special inputs created by [track_usage\(\)](#) are available in server and optionally logs are printed in console.

Usage

```
store_null(console = TRUE)
```

Arguments

console Print logs in R console.

Value

A list that can be used in [track_usage\(\)](#).

Examples

```
library(shiny)
library(shinylogs)

ui <- fluidPage(
  tags$h2("Record inputs change"),
  fluidRow(
    column(
      width = 3,
      selectInput(
        inputId = "select",
        label = "Select input",
        choices = month.name
      ),
      numericInput(
        inputId = "numeric",
        label = "Numerci input",
        value = 4,

```



```

      min = 0, max = 20
    ),
    checkboxGroupInput(
      inputId = "checkboxGroup",
      label = "Checkbox group input",
      choices = LETTERS[1:5]
    ),
    sliderInput(
      inputId = "slider",
      label = "Slider input",
      min = 0, max = 100, value = 50
    )
  ),
  column(
    width = 9,
    tags$b("Last input:"),
    verbatimTextOutput(outputId = "last_input"),
    tags$b("All inputs:"),
    verbatimTextOutput(outputId = "all_inputs")
  )
)
)
)

server <- function(input, output, session) {

  track_usage(
    storage_mode = store_null() # dont store on disk
  )

  output$last_input <- renderPrint({
    input$.shinylogs_lastInput # last input triggered
  })

  output$all_inputs <- renderPrint({
    input$.shinylogs_input # all inputs that have changed
  })

}

if (interactive())
  shinyApp(ui, server)

```

store_rds

Use RDS files as storage mode

Description

One RDS will be written for each session of the application.

Usage

```
store_rds(path)
```

Arguments

path Path where to write RDS files.

Value

A list that can be used in [track_usage\(\)](#).

Examples

```
library(shiny)
library(shinylogs)

# temp directory for writing logs
tmp <- tempdir()

# when app stop,
# navigate to the directory containing logs
onStop(function() {
  browseURL(url = tmp)
})

# Classir Iris clustering with Shiny
ui <- fluidPage(

  headerPanel("Iris k-means clustering"),

  sidebarLayout(
    sidebarPanel(
      selectInput(
        inputId = "xcol",
        label = "X Variable",
        choices = names(iris)
      ),
      selectInput(
        inputId = "ycol",
        label = "Y Variable",
        choices = names(iris),
        selected = names(iris)[[2]]
      ),
      numericInput(
        inputId = "clusters",
        label = "Cluster count",
        value = 3,
        min = 1,
        max = 9
      )
    ),
    mainPanel(
```

```

        plotOutput("plot1")
      )
    )
  )

server <- function(input, output, session) {

  # Store RDS with logs in the temp dir
  track_usage(
    storage_mode = store_rds(path = tmp)
  )

  # classic server logic

  selectedData <- reactive({
    iris[, c(input$xcol, input$ycol)]
  })

  clusters <- reactive({
    kmeans(selectedData(), input$clusters)
  })

  output$plot1 <- renderPlot({
    palette(c("#E41A1C", "#377EB8", "#4DAF4A", "#984EA3",
              "#FF7F00", "#FFFF33", "#A65628", "#F781BF", "#999999"))

    par(mar = c(5.1, 4.1, 0, 1))
    plot(selectedData(),
          col = clusters()$cluster,
          pch = 20, cex = 3)
    points(clusters()$centers, pch = 4, cex = 4, lwd = 4)
  })

}

if (interactive())
  shinyApp(ui, server)

```

store_sqlite

Use SQLite database as storage mode

Description

All logs will be written in the same file.

Usage

```
store_sqlite(path)
```

Arguments

path Path to the SQLite file or a directory where to create one.

Value

A list that can be used in `track_usage()`.

Examples

```
if (interactive()) {  
  
  library(shiny)  
  library(shinylogs)  
  
  # temp directory for writing logs  
  tmp <- tempdir()  
  
  # when app stop,  
  # navigate to the directory containing logs  
  onStop(function() {  
    browseURL(url = tmp)  
  })  
  
  # Classir Iris clustering with Shiny  
  ui <- fluidPage(  
  
    headerPanel("Iris k-means clustering"),  
  
    sidebarLayout(  
      sidebarPanel(  
        selectInput(  
          inputId = "xcol",  
          label = "X Variable",  
          choices = names(iris)  
        ),  
        selectInput(  
          inputId = "ycol",  
          label = "Y Variable",  
          choices = names(iris),  
          selected = names(iris)[[2]]  
        ),  
        numericInput(  
          inputId = "clusters",  
          label = "Cluster count",  
          value = 3,  
          min = 1,  
          max = 9  
        )  
      ),  
      mainPanel(  
        plotOutput("plot1")  
      )  
    )  
  )  
}
```

```

    )
  )

  server <- function(input, output, session) {

    # Store RDS with logs in the temp dir
    track_usage(
      storage_mode = store_sqlite(path = tmp)
    )

    # classic server logic

    selectedData <- reactive({
      iris[, c(input$xcol, input$ycol)]
    })

    clusters <- reactive({
      kmeans(selectedData(), input$clusters)
    })

    output$plot1 <- renderPlot({
      palette(c("#E41A1C", "#377EB8", "#4DAF4A", "#984EA3",
                "#FF7F00", "#FFFF33", "#A65628", "#F781BF", "#999999"))

      par(mar = c(5.1, 4.1, 0, 1))
      plot(selectedData(),
            col = clusters()$cluster,
            pch = 20, cex = 3)
      points(clusters()$centers, pch = 4, cex = 4, lwd = 4)
    })

  }

  shinyApp(ui, server)
}

```

 track_usage

Track usage of a Shiny app

Description

Used in Shiny server it will record all inputs and output changes and errors that occurs through an output.

Usage

```

track_usage(
  storage_mode,
  what = c("session", "input", "output", "error"),

```

```

exclude_input_regex = NULL,
exclude_input_id = NULL,
on_unload = FALSE,
app_name = NULL,
exclude_users = NULL,
get_user = NULL,
dependencies = TRUE,
session = getDefaultReactiveDomain()
)

```

Arguments

storage_mode	Storage mode to use : <code>store_json()</code> , <code>store_rds()</code> , <code>store_sqlite()</code> or <code>store_null()</code> .
what	Elements to record between "session", "input", "output" and "error".
exclude_input_regex	Regular expression to exclude inputs from tracking.
exclude_input_id	Vector of inputId to exclude from tracking.
on_unload	Logical, save log when user close the browser window or tab, if TRUE it prevent to create shinylogs input during normal use of the application, there will be created only on close, downside is that a popup will appear asking to close the page.
app_name	Name of the app as a character string. If NULL, <code>basename(getwd())</code> (name of the folder where application is located) is used.
exclude_users	Character vectors of user for whom it is not necessary to save the log.
get_user	A function to get user name, it should return a character and take one argument: the Shiny session.
dependencies	Load dependencies in client, can be set to FALSE if <code>use_tracking()</code> has been called in UI.
session	The shiny session.

Note

The following inputs will be accessible in the server:

- **.shinylogs_lastInput** : last input used by the user
- **.shinylogs_input** : all inputs send from the browser to the server
- **.shinylogs_error** : all errors generated by outputs elements
- **.shinylogs_output** : all outputs generated from the server
- **.shinylogs_browserData** : information about the browser where application is displayed.

Examples

```

# Save logs on disk -----
if (interactive()) {

```

```
# temporary directory for writing logs
tmp <- tempdir()

# when app stop,
# navigate to the directory containing logs
onStop(function() {
  browseURL(url = tmp)
})

# Classic Iris clustering with Shiny
ui <- fluidPage(

  headerPanel("Iris k-means clustering"),

  sidebarLayout(
    sidebarPanel(
      selectInput(
        inputId = "xcol",
        label = "X Variable",
        choices = names(iris)
      ),
      selectInput(
        inputId = "ycol",
        label = "Y Variable",
        choices = names(iris),
        selected = names(iris)[[2]]
      ),
      numericInput(
        inputId = "clusters",
        label = "Cluster count",
        value = 3,
        min = 1,
        max = 9
      )
    ),
    mainPanel(
      plotOutput("plot1")
    )
  )
)

server <- function(input, output, session) {

  # Store JSON with logs in the temp dir
  track_usage(
    storage_mode = store_json(path = tmp)
  )

  # classic server logic

  selectedData <- reactive({
    iris[, c(input$xcol, input$ycol)]
  })
}
```

```

    })

    clusters <- reactive({
      kmeans(selectedData(), input$clusters)
    })

    output$plot1 <- renderPlot({
      palette(c("#E41A1C", "#377EB8", "#4DAF4A", "#984EA3",
                "#FF7F00", "#FFFF33", "#A65628", "#F781BF", "#999999"))

      par(mar = c(5.1, 4.1, 0, 1))
      plot(selectedData(),
            col = clusters()$cluster,
            pch = 20, cex = 3)
      points(clusters()$centers, pch = 4, cex = 4, lwd = 4)
    })

  }

  shinyApp(ui, server)
}

# Logs in console & special inputs -----

if (interactive()) {
  library(shiny)
  library(shinylogs)

  ui <- fluidPage(
    tags$h2("Record inputs change"),
    fluidRow(
      column(
        width = 3,
        selectInput(
          inputId = "select",
          label = "Select input",
          choices = month.name
        ),
        numericInput(
          inputId = "numeric",
          label = "Numerci input",
          value = 4,
          min = 0, max = 20
        ),
        checkboxGroupInput(
          inputId = "checkboxGroup",
          label = "Checkbox group input",
          choices = LETTERS[1:5]
        ),
        sliderInput(
          inputId = "slider",
          label = "Slider input",

```



```

        min = 0, max = 100, value = 50
      )
    ),
    column(
      width = 9,
      tags$b("Last input triggered:"),
      verbatimTextOutput(outputId = "last_input"),
      tags$b("All inputs:"),
      verbatimTextOutput(outputId = "all_inputs")
    )
  )
)

server <- function(input, output, session) {

  # dont store on disk, just show in R console
  track_usage(
    storage_mode = store_null()
  )

  # last input triggered
  output$last_input <- renderPrint({
    input$.shinylogs_lastInput
  })

  # all inputs that have changed
  output$all_inputs <- renderPrint({
    input$.shinylogs_input
  })

}

shinyApp(ui, server)
}

```

 use_tracking

Insert dependencies to track usage of a Shiny app

Description

If used in UI of an application, this will create new inputs available in the server. Set dependencies = FALSE in `track_usage()` server-side to load dependencies only once.

Usage

```

use_tracking(
  what = c("session", "input", "output", "error"),
  exclude_input_regex = NULL,
  exclude_input_id = NULL,
  on_unload = FALSE,

```

```

    app_name = NULL
  )

```

Arguments

what	Elements to record between "session", "input", "output" and "error".
exclude_input_regex	Regular expression to exclude inputs from tracking.
exclude_input_id	Vector of inputId to exclude from tracking.
on_unload	Logical, save log when user close the browser window or tab, if TRUE it prevent to create shinylogs input during normal use of the application, there will be created only on close, downside is that a popup will appear asking to close the page.
app_name	Name of the app as a character string. If NULL, basename(getwd()) (name of the folder where application is located) is used.

Note

The following inputs will be accessible in the server (according to what is used in record argument):

- **.shinylogs_lastInput** : last input used by the user
- **.shinylogs_input** : all inputs send from the browser to the server
- **.shinylogs_error** : all errors generated by outputs elements
- **.shinylogs_output** : all outputs generated from the server
- **.shinylogs_browserData** : information about the browser where application is displayed.

Examples

```

if (interactive()) {

  library(shiny)
  library(shinylogs)

  ui <- fluidPage(

    # Load tracking dependencies
    use_tracking(),

    splitLayout(
      cellArgs = list(style = "height: 250px"),
      radioButtons("radio", "Radio:", names(iris)),
      checkboxGroupInput("checkbox", "Checkbox:", names(iris)),
      selectInput("select", "Select:", names(iris))
    ),

    tags$p("Last input used, the 'name' slot correspond to inputId:"),
    verbatimTextOutput("last")
  )
}

```

```
)  
server <- function(input, output, session) {  
  output$last <- renderPrint({  
    input$.shinylogs_lastInput  
  })  
}  
shinyApp(ui, server)  
}
```

Index

`read_json_logs`, [2](#)
`read_rds_logs`, [3](#)

`store_custom`, [3](#)
`store_gogledrive`, [5](#)
`store_json`, [6](#)
`store_json()`, [14](#)
`store_null`, [8](#)
`store_null()`, [14](#)
`store_rds`, [9](#)
`store_rds()`, [14](#)
`store_sqlite`, [11](#)
`store_sqlite()`, [14](#)

`track_usage`, [13](#)
`track_usage()`, [4–6, 8, 10, 12, 17](#)

`use_tracking`, [17](#)
`use_tracking()`, [14](#)