

GGBase

November 11, 2009

R topics documented:

genesym-class	1
featureFilter	2
GGBase-package	3
gwSnpScreenResult-class	3
MAFilter	4
multiCisTestResult-class	5
plot_EvG-methods	6
SessionInfo-class	6
smlSet-class	7
smlSummary	8
snpLocs.Hs	9
snpsNear	10
Index	12

genesym-class	<i>Class "genesym" and other casting classes</i>
---------------	--------------------------------------------------

Description

classes that help establish symbol semantics for dispatching

Objects from the Class

Objects can be created by calls of the form `new("genesym", ...)`. and generally just extend character or numeric so that vector operations are straightforward

Currently, `genesym` is used to allow HUGO symbols to be passed to `[]`; `chrnum` identifies numerals or numeric constants as indices into the set of chromosomes (no chr prefix is allowed); `rsid` identifies dbSNP identifiers; `probeId` identifies a string as a microarray probe identifier.

`snpdepth` identifies a number that will be used as the number of chromosome-specific test results to be retained in any genome-wide screen

Slots

.Data: Object of class "character" ~~

Extends

Class "[character](#)", from data part. Class "[vector](#)", by class "character", distance 2. Class [characterORMIAME](#), by class "character", distance 2.

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
showClass("genesym")
genesym("CPNE1")
```

featureFilter	<i>remove unannotated or undesired features from an smlSet instance</i>
---------------	-------------------------------------------------------------------------

Description

remove unannotated or undesired features from an smlSet instance

Usage

```
featureFilter(x, requires = c("loc", "autosomal"))
```

Arguments

x	instance of smlSet class
requires	character vector – if "loc" is present, require that a non-NA value is present in CHRLOC for each feature; if "autosomal" is present, require that CHR value is in 1:22 (presently assumes human genome)

Value

revised smlSet instance excluding features no

Author(s)

VJ Carey

Examples

```
library(GGtools)
if (!exists("hmceuB36.2021")) data(hmceuB36.2021)
dim(exprs(hmceuB36.2021))
ff = featureFilter(hmceuB36.2021)
dim(exprs(ff))
```

Description

GGbase Package Overview

Details

This package provides infrastructure for programming related to the genetics of gene expression. The GGtools package makes use of classes and methods defined in this package. GGdata and hmyriB36 packages use the class structures defined in this package for serialized data.

Introductory information is available from vignettes, type `openVignette()`.

Full listing of documented man pages is available in HTML view by typing `help.start()` and selecting GGbase package from the Packages menu or via `library(help="GGbase")`.

Author(s)

V. Carey

`gwSnpScreenResult-class`

Class "gwSnpScreenResult" – containers for GGtools gwSnpScreen method outputs and allied objects

Description

Class "gwSnpScreenResult" – container for GGtools gwSnpScreen method outputs and allied objects

Objects from the Class

Objects can be created by calls of the form `new("gwSnpScreenResult", ...)`. These will be primarily lists of inference tables (snps are rows, columns are statistics and p-values). Additional slots manage analysis metadata.

`gwSnpScreenResult` is intended for genome-wide analysis of expression for a single gene.

`cwSnpScreenResult` is intended for the restriction to a single chromosome.

`multiGwSnpScreenResult` is intended for analyses with multiple genes.

Because the vast majority of tests are uninformative, early filtering is important for managing object sizes. Instances of `filteredGwSnpScreenResult` and `filteredMultiGwSnpScreenResult` are created when a `snpdepth` parameter is used with `gwSnpTests`.

Slots

- .Data:** Object of class "list" containing inference tables (snps are rows, columns are statistics and p-values)
- gene:** Object of class "character" typically the HUGO symbol of the gene analyzed
- psid:** Object of class "character" the feature identifier of the associated microarray
- annotation:** Object of class "character" vector of relevant annotation package identifier names
- formula:** Object of class "formula" the formula used to fit the model relating expression to genotype

Extends

Class "list", from data part. Class "vector", by class "list", distance 2. Class [AssayData](#), by class "list", distance 2.

Methods

plot and show

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
showClass("gwSnpScreenResult")
showClass("cwSnpScreenResult")
```

MAFfilter

restrict SNP in an smlSet to range of minor allele frequencies (MAF)

Description

restrict SNP in an smlSet to range of minor allele frequencies (MAF)

Usage

```
MAFfilter(x, lower = 0, upper = 1)
```

Arguments

x	smlSet instance
lower	numeric lower bound on minor allele frequency for keeping a SNP
upper	numeric upper bound on minor allele frequency for keeping a SNP

Details

uses [snp.matrix-class](#) summary method from snpMatrix

Value

revised instance of `smlSet-class`

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
library(GGtools)
if (!exists("hmceuB36.2021")) data(hmceuB36.2021)
sapply(smList(MAFfilter(hmceuB36.2021, lower=.1)), dim)
```

```
multiCisTestResult-class
      Class "multiCisTestResult"
```

Description

object to contain results of restricted gene-centric searches for eQTL

Objects from the Class

Objects can be created by calls of the form `new("multiCisTestResult", ...)`.

Slots

.Data: Object of class "list" – list of results of `snp.rhs.tests`

conditions: Object of class "list" – list of runtime conditions encountered

call: Object of class "call" – for auditing, the call used is saved

Extends

Class "list", from data part. Class "vector", by class "list", distance 2. Class "AssayData", by class "list", distance 2.

Methods

`show` signature(object = "multiCisTestResult"):...

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
showClass("multiCisTestResult")
```

`plot_EvG-methods` *formal method for visualizing expression distributions vs genotype*

Description

boxplot expression vs genotype

Methods

gsym = "genesym", rsid = "rsid", sms = "smlSet" generates an annotated boxplot

multisnp methods `plot_EvG2` allows specification of a second SNP rsid and shows boxplots over the cross-tabulation of the allele combinations

Examples

```
library(GGtools)
data(hmceuB36.2021)
plot_EvG(genesym("CPNE1"), rsid("rs6060535"), hmceuB36.2021)
```

`SessionInfo-class` *Class "SessionInfo" – objects to help stamp an output with information on session state*

Description

Class "SessionInfo" – objects to help stamp an output with information on session state

Objects from the Class

Objects can be created by calls of the form `new("SessionInfo", ...)`.

Slots

.S3Class: Object of class "character" simple cast to allow checking

Extends

Class "[oldClass](#)", by class "sessionInfo", distance 2.

Methods

No methods defined with class "SessionInfo" in the signature.

Examples

```
showClass("SessionInfo")
```

smlSet-class	<i>Documentation on S4 class "smlSet" an eSet-derived container for snpMatrix lists, allowing efficient combination of SNP chip genotyping with microarray expression data, and allied classes</i>
--------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Description

Documentation on S4 class "smlSet" an eSet-derived container for snpMatrix lists, allowing efficient combination of SNP chip genotyping with microarray expression data, and allied classes

Objects from the Class

Objects can be created by calls of the form `new("smlSet", assayData, phenoData, featureData, experimentData, annotation, ...)`. These objects respond to interrogation on samples, expression values, SNP values, and other metadata.

Slots

smlEnv: Object of class "environment" an environment with single key `smlList` pointing to a list of package `snpMatrix` `snp.matrix` instances

organism: Object of class "character" informal, "Hs" recommended for human

assayData: Object of class "AssayData" intended to hold expression data coordinated with the `smlEnv` data

phenoData: Object of class "AnnotatedDataFrame" standard sample-level data container from eSet design

featureData: Object of class "AnnotatedDataFrame" standard feature-level metadata container, implied usage is for documenting the expression data elements

experimentData: Object of class "MIAME" standard metadata container from Biobase eSet design

annotation: Object of class "character" vector giving the Bioconductor annotation package (.db type) for decoding expression feature identifiers.

.__classVersion__: Object of class "Versions" class version tracking metadata

Extends

Class `eSet`, directly. Class `VersionedBiobase`, by class "eSet", distance 2. Class `Versioned`, by class "eSet", distance 3.

Methods

smlList signature(`x = "smlSet"`): retrieves the actual list of `snp.matrix` entities

smlEnv signature(`x = "smlSet"`): retrieves the environment holding `snp.matrix` entities

exprs signature(`x = "smlSet"`): retrieves the matrix of expression values

snp signature(`x = "smlSet"`, `chr = "chrnum"`): retrieves the raw matrix of genotype values (`snp.matrix` instance from `snpMatrix` package)

combine: concatenates expression data and forms intersection of SNP sets

getAlleles(smlSet, rsid): returns A/B notations for SNP determined by `rsid`

Note

We have included a `[` method for `snp.matrix` instances that accepts an `rsid` instance as a column selector.

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

See Also

GGtools package makes extensive use of these classes and methods.

Examples

```
showClass("smlSet")
```

<code>smlSummary</code>	<i>class and function to summarize frequency information on genotypes in an smlSet</i>
-------------------------	----------------------------------------------------------------------------------------

Description

generates information on sample size, minor allele frequency, specific call frequencies, and HWE test results on all SNP in an `smlSet`

Usage

```
smlSummary(x)
```

Arguments

`x` instance of `smlSet-class`

Details

to control volume of printout a simple list extending class is defined for show method

Value

Instance of `smlSummary` class, which simply extends list. Each list element is a matrix of results provided by `summary`, `snp.matrix-method`.

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
library(GGtools)
if (!exists("hmceuB36.2021")) data(hmceuB36.2021)
smlSummary(hmceuB36.2021)
```

snpLocs.Hs	<i>SNP location accessor</i>
------------	------------------------------

Description

SNP location accessor

Usage

```
snpLocs.Hs(cnum, rsid)
```

Arguments

cnum	chrnum instance indicating chromosome
rsid	rsid instance giving dbSNP ids for snps of interest

Details

The SNPlocs.Hsapiens.dbSNP.* package is curated by Bioconductor and maintains location and allele information on SNP.

The hsSnpLocs environment is available through data(hsSnpLocs), and contains a unified representation of the information in the SNPlocs package (which is only available through various chromosome-specific calls).

Value

two-row matrix – top row is numeric suffix of dbSNP ids, bottom row is location, genome-wide if chrnum is missing

Author(s)

Vince Carey <stvjc@channing.harvard.edu>

Examples

```
library(GGtools)
data(hmceuB36.2021)
nn21 = colnames(smList(hmceuB36.2021)[["21"]])
length(nn21)
ss = snpLocs.Hs(chrnum(21), rsid(nn21))
dim(ss)
# notes that the locations available are not completely
# congruent with those asserted in HapMap data
```

snpsNear *obtain list of rs numbers for snps near a gene*

Description

obtain list of rs numbers for snps near a gene

Usage

```
snpsNear(sym, radius=1e+05, chrnum, ...)
```

Arguments

sym	instance of genesym class [e.g., use genesym(string) for gene 'string'], or of rsid class, or of numeric class. An instance of <code>GSEABase-class</code> can also be supplied if it has geneIdType AnnotationIdentifier.
radius	number of base-pairs in each direction to look
chrnum	chrnum instance .. optional
...	options not now in use

Details

simple arithmetic based on output of snpLocs.Hs

Value

character vector of rsxxxxxx, dbSNP id, according to locations from SNPlocs.Hsapiens.dbSNP.20071016 package, as transferred to snpLocs.Hs resource in GGBase

note that an attribute 'target' is returned, a named vector with components chr and loc describing chromosome and location of the target for which nearby SNPs are sought

Note

first invocation can take longer than subsequent, if snpLocs.Hs has not been invoked previously

Author(s)

Vince Carey <stvjc@channing.harvard.edu>

Examples

```
nearc = snpsNear(genesym("CPNE1"), 10000, chrnum(20))
library(GGtools)
data(hmceuB36.2021)
ss = smList(hmceuB36.2021)[[1]]
# following calculation requires new "[" for j an instance of rsid
clo = ss[ , rsid(snpsNear(rsid("rs6060535"), rad=1500, chrnum(20))) ]
clo
# try a gene set
library(GSEABase)
s1 = GeneSet(c("CPNE1", "ADA"), geneIdType=SymbolIdentifier())
s2 = s1
```

```
geneIdType(s2) = AnnotationIdentifier("illuminaHumanv1.db")
s2
sapply(snpsNear(s2), length)
```

Index

*Topic classes

genesym-class, 1
 gwSnpScreenResult-class, 3
 multiCisTestResult-class, 5
 SessionInfo-class, 6
 smlSet-class, 6

*Topic methods

plot_EvG-methods, 5

*Topic models

featureFilter, 2
 MAFilter, 4
 smlSummary, 8
 snpLocs.Hs, 8
 snpsNear, 9

*Topic package

GGbase-package, 2
 [, gwSnpScreenResult, ANY, ANY, ANY-method
 (gwSnpScreenResult-class),
 3
 [, gwSnpScreenResult, ANY, ANY, ANY-method
 (gwSnpScreenResult-class),
 3
 [, smlSet, ANY, ANY, ANY-method
 (smlSet-class), 6
 [, snp.matrix, ANY, rsid, ANY-method
 (smlSet-class), 6

AssayData, 3, 5

character, 1
 characterORMIAME, 1
 chrnum (genesym-class), 1
 chrnum, character-method
 (genesym-class), 1
 chrnum, numeric-method
 (genesym-class), 1
 chrnum-class (genesym-class), 1
 cnumOrMissing (genesym-class), 1
 cnumOrMissing-class
 (genesym-class), 1

combine, filteredMultiGwSnpScreenResult-class, 3
 combine, multiGwSnpScreenResult, multiGwSnpScreenResult-method
 (gwSnpScreenResult-class),
 3
 combine, smlSet, smlSet-method
 (smlSet-class), 6
 cwSnpScreenResult-class
 (gwSnpScreenResult-class),
 3
 eSet, 7
 exprs, smlSet-method
 (smlSet-class), 6
 featureFilter, 2
 filteredGwSnpScreenResult-class
 (gwSnpScreenResult-class),
 3
 filteredMultiGwSnpScreenResult-class
 (gwSnpScreenResult-class),
 3
 genesym (genesym-class), 1
 genesym, character-method
 (genesym-class), 1
 genesym-class, 1
 getAlleles (smlSet-class), 6
 getAlleles, smlSet, rsid-method
 (smlSet-class), 6
 getSnpLocs (snpLocs.Hs), 8
 getSnpLocs, smlSet, chrnum-method
 (snpLocs.Hs), 8
 getSnpLocs, smlSet, missing-method
 (snpLocs.Hs), 8
 GGbase (GGbase-package), 2
 GGbase-package, 2
 GSEABase-class, 9
 gwSnpScreenResult
 (gwSnpScreenResult-class),
 3
 gwSnpScreenResult-class, 3
 list, 3, 5

- MAFilter, 4
- multiCisTestResult-class, 5
- multiGwSnpScreenResult-class
 - (gwSnpScreenResult-class), 3
- oldClass, 6
- phenoVar (genesym-class), 1
- phenoVar, character-method
 - (genesym-class), 1
- phenoVar-class (genesym-class), 1
- plot, cwSnpScreenResult, ANY-method
 - (gwSnpScreenResult-class), 3
- plot, gwSnpScreenResult, ANY-method
 - (gwSnpScreenResult-class), 3
- plot, multiGwSnpScreenResult, ANY-method
 - (gwSnpScreenResult-class), 3
- plot_EvG (plot_EvG-methods), 5
- plot_EvG, genesym, rsid, smlSet-method
 - (plot_EvG-methods), 5
- plot_EvG, probeId, rsid, smlSet-method
 - (plot_EvG-methods), 5
- plot_EvG-methods, 5
- plot_EvG2 (plot_EvG-methods), 5
- plot_EvG2, genesym, rsid, rsid, smlSet-method
 - (plot_EvG-methods), 5
- plot_EvG2, probeId, rsid, rsid, smlSet-method
 - (plot_EvG-methods), 5
- probeId (genesym-class), 1
- probeId, character-method
 - (genesym-class), 1
- probeId-class (genesym-class), 1
- rsid (genesym-class), 1
- rsid, character-method
 - (genesym-class), 1
- rsid, numeric-method
 - (genesym-class), 1
- rsid-class (genesym-class), 1
- SessionInfo-class, 6
- show, chrnum-method
 - (genesym-class), 1
- show, cwSnpScreenResult-method
 - (gwSnpScreenResult-class), 3
- show, filteredGwSnpScreenResult-method
 - (gwSnpScreenResult-class), 3
- show, filteredMultiGwSnpScreenResult-method
 - (gwSnpScreenResult-class), 3
- show, gwSnpScreenResult-method
 - (gwSnpScreenResult-class), 3
- show, multiCisTestResult-method
 - (multiCisTestResult-class), 5
- show, multiGwSnpScreenResult-method
 - (gwSnpScreenResult-class), 3
- show, rsid-method (genesym-class), 1
- show, smlSet-method
 - (smlSet-class), 6
- show, smlSummary-method
 - (smlSummary), 8
- show, snpLocs-method (snpLocs.Hs), 8
- smlEnv (smlSet-class), 6
- smlEnv, smlSet-method
 - (smlSet-class), 6
- smlList (smlSet-class), 6
- smlList, smlSet-method
 - (smlSet-class), 6
- smlSet (smlSet-class), 6
- smlSet-class, 4, 8
- smlSet-class, 6
- smlSummary, 8
- smlSummary-class (smlSummary), 8
- snp.matrix-class, 4
- snp.rhs.tests, 5
- snpdepth (genesym-class), 1
- snpdepth-class (genesym-class), 1
- snpLocs-class (snpLocs.Hs), 8
- snpLocs.Hs, 8
- snpLocs.Hs, chrnum, missing-method
 - (snpLocs.Hs), 8
- snpLocs.Hs, chrnum, rsid-method
 - (snpLocs.Hs), 8
- snpLocs.Hs, chrnum.missing-method
 - (snpLocs.Hs), 8
- snpLocs.Hs, chrnum.rsid-method
 - (snpLocs.Hs), 8
- snpLocs.Hs, missing, rsid-method
 - (snpLocs.Hs), 8
- snpLocs.Hs, rsid, ANY-method
 - (snpLocs.Hs), 8
- snpLocs.Hs, rsid-method
 - (snpLocs.Hs), 8
- snpLocs.Hs, sid, ANY-method

(snpLocs.Hs), 8
snpNames (*smlSet-class*), 6
snpNames, *smlSet*, *chrnum*-method
 (*smlSet-class*), 6
snpNames, *smlSet*, *missing*-method
 (*smlSet-class*), 6
snps (*smlSet-class*), 6
snps, *smlSet*, *chrnum*-method
 (*smlSet-class*), 6
snpsNear, 9
summary, *snp.matrix*-method, 8

vector, 1, 3, 5
Versioned, 7
VersionedBiobase, 7