

tspair

November 11, 2009

R topics documented:

dat2	1
dat	2
eSet1	2
eSet2	2
grp	3
plot.tsp	3
predict.tsp	4
summary.tsp	5
ts.pair	6
tspcalc	7
tspdata	9
tsplot	9
tspsig	10
Index	12

dat2	<i>Simulated gene expression data.</i>
------	--

Description

This data set is a simulated gene expression matrix "dat2" with 500 genes and 20 arrays used for testing predictions based on the data "dat"

Usage

dat2

Format

matrix

dat	<i>Simulated gene expression data.</i>
-----	--

Description

This data set is a simulated gene expression matrix "dat" with 1000 genes and 50 arrays.

Usage

dat

Format

matrix

eSet1	<i>A simulated expression set.</i>
-------	------------------------------------

Description

This is a simulated expression set, where $\text{exprs}(\text{eSet1}) = \text{dat}$ and $\text{pData}(\text{eSet1}) = \text{grp}$.

Usage

eSet1

Format

Expression Set

eSet2	<i>A simulated expression set.</i>
-------	------------------------------------

Description

This is a simulated test texpression set, where $\text{exprs}(\text{eSet2}) = \text{dat2}$.

Usage

eSet2

Format

Expression Set

grp	<i>A group indicator.</i>
-----	---------------------------

Description

This is a group indicator for the simulated gene expression data "dat" in the TSP package. The two groups are "healthy" and "diseased".

Usage

```
grp
```

Format

```
vector
```

plot.tsp	<i>Graphical display of tsp objects</i>
----------	---

Description

Graphical display of tsp objects

Usage

```
## S3 method for class 'tsp':  
plot(x, y, ...)
```

Arguments

x	A tsp object
y	Not used
...	Plotting arguments, not used

Details

tspplot() creates a plot of each top scoring pair. The figure plots the expression for the first gene in the TSP pair versus the expression for the second gene in the TSP pair across arrays. The user defined groups are plotted in the colors red and blue. The score for the pair is shown across the top of each plot. If there is more than one TSP, hitting return will cycle from one TSP to the next.

Value

Nothing of interest.

Author(s)

Jeffrey T. Leek <jtleek@jhu.edu>

References

D. Geman, C. d'Avignon, D. Naiman and R. Winslow, "Classifying gene expression profiles from pairwise mRNA comparisons, *Statist. Appl. in Genetics and Molecular Biology*, 3, 2004.

See Also

[tspcalc](#), [ts.pair](#), [tspsig](#), [predict.tsp](#), [summary.tsp](#), [tspplot](#)

Examples

```
## Not run:
## Load data
data(tspdata)
tsp1 <- tspcalc(dat, grp)
plot(tsp1)

## End(Not run)
```

<code>predict.tsp</code>	<i>Prediction based on a tsp object</i>
--------------------------	---

Description

This function can be used to predict outcome values for a data set based on a tsp object.

Usage

```
## S3 method for class 'tsp':
predict(object, dat=NULL, select=NULL, ...)
```

Arguments

<code>object</code>	A tsp object
<code>dat</code>	Can take two values: (a) an m genes by n arrays matrix of expression data or (b) an eSet object
<code>select</code>	An indicator of which TSP to use, defaults to the first TSP.
<code>...</code>	Plotting arguments (ignored)

Details

`predict()` accepts a tsp object calculated on an expression set or gene expression matrix. If no other data set is included, the tsp predictions for the original data set are produced. If a second gene expression matrix or expression set is included, `predict()` looks for the gene names of the TSP in `tspobj` and attempts to match them in the `rownames` or `featureNames` of the gene expression matrix. If `rownames` or `featureNames` are not available, the prediction is based on the row numbers. If a match is identified, `predict()` makes a prediction for each gene based on the output.

Value

<code>predict</code>	A class prediction for each array of <code>dat</code> based on the TSP from <code>tspobj</code>
----------------------	---

Author(s)

Jeffrey T. Leek <jtleek@jhu.edu>

References

D. Geman, C. d'Avignon, D. Naiman and R. Winslow, "Classifying gene expression profiles from pairwise mRNA comparisons," *Statist. Appl. in Genetics and Molecular Biology*, 3, 2004.

A.C. Tan, D.Q. Naiman, L. Xu, R.L. Winslow, D. Geman, "Simple decision rules for classifying human cancers from gene expression profiles," *Bioinformatics*, 21:3896-3904, 2005.

See Also

[tspplot](#), [ts.pair](#), [tspcalc](#), [tspsig](#), [summary.tsp](#)

Examples

```
## Not run:
## Load data
data(tspdata)

## Run tspcalc() on a data matrix and grp vector
tsp1 <- tspcalc(dat,grp)

## Get predictions for a new eSet or data matrix
predict.tsp(tsp1,dat2,1)
predict(tsp1,eSet2,1)
## End(Not run)
```

summary.tsp

Summary of a tsp object

Description

This function can be used to summarize a TSP object.

Usage

```
## S3 method for class 'tsp':
summary(object, select=NULL, printall=FALSE, ...)
```

Arguments

object	A tsp object
select	A numerical indicator of which TSP to summarize, if NULL, all TSPs are summarized one at a time
printall	If printall=TRUE all TSPs are summarized at once
...	Summary arguments (ignored)

Details

summary() accepts a tsp object calculated on an expression set or gene expression matrix. The result is a table of frequencies for the TSP indicator versus the group indicator.

Value

A table.

Author(s)

Jeffrey T. Leek <jtleek@jhu.edu>

References

D. Geman, C. d'Avignon, D. Naiman and R. Winslow, "Classifying gene expression profiles from pairwise mRNA comparisons," *Statist. Appl. in Genetics and Molecular Biology*, 3, 2004.

See Also

[tspplot](#), [ts.pair](#), [tspcalc](#), [tspsig](#), [predict.tsp](#)

Examples

```
## Not run:
## Load data
data(tspdata)

## Run tspcalc() on a data matrix and grp vector
tsp1 <- tspcalc(dat,grp)

## Get the summary for the tsp object.
summary(tsp1)
summary.tsp(tsp1)
## End(Not run)
```

ts.pair

Calculation of top scoring pairs.

Description

This function calculates the pair of genes that show the maximum difference in ranking between two user specified groups. The function `tspcalc()` is the general version of this function that accepts `eSets`.

Usage

```
ts.pair(dat, grp)
```

Arguments

dat	An m genes by n arrays matrix of expression data.
grp	A group indicator with values 0 and 1 for the two groups.

Details

`ts.pair()` only works for two group classification. All the caveats for `tspcalc()` apply here, but this function only works for matrix and vector arguments, for a more general function see `tspcalc()`. The top scoring pairs methodology was originally described in Geman et al. (2004). and the unique TSP idea was described in Tan et al. (2005).

Value

A tsp object with elements:

index	A two-column matrix where each row is a pair of indices from the data matrix achieving the top score
tspscore	The rank based score described in Geman et al. (2004), essentially the empirical average of sensitivity and specificity for the pair.
score	The tie-breaking score described in Tan et al. (2005).
grp	The binary group indicator.
tspdat	Row i and row (i + Number of total TSPs) of this data matrix represent the expression data for the ith TSP pair.
labels	The group labels for the two groups as defined by the grp variable.

Author(s)

Jeffrey T. Leek <jtleek@jhu.edu>

References

D. Geman, C. d'Avignon, D. Naiman and R. Winslow, "Classifying gene expression profiles from pairwise mRNA comparisons," *Statist. Appl. in Genetics and Molecular Biology*, 3, 2004.

A.C. Tan, D.Q. Naiman, L. Xu, R.L. Winslow, D. Geman, "Simple decision rules for classifying human cancers from gene expression profiles," *Bioinformatics*, 21: 3896-3904, 2005.

See Also

[tspplot](#), [tspcalc](#), [tspsig](#), [predict.tsp](#), [summary.tsp](#)

Examples

```
## Not run:
## Load data
data(tspdata)
tsp1 <- ts.pair(dat, grp)
tsp1$index

## End(Not run)
```

tspcalc

Estimate top scoring pairs from a gene expression matrix

Description

This function calculates the pair of genes that show the maximum difference in ranking between two user specified groups. The "top scoring pair" (TSP) maximizes the average of sensitivity and specificity over all rank based classifiers using a pair of genes in the data set.

Usage

```
tspcalc(dat, grp)
```

Arguments

dat	Can take two values: (a) an m genes by n arrays matrix of expression data or (b) an eSet object
grp	Can take one of two values: (a) A group indicator in character or numeric form, (b) an integer indicating the column of pData(dat) to use as the group indicator.

Details

tspcalc only works for two group classification. The computation time grows rapidly in the number of genes, so for large gene expression matrices one should be prepared to wait or do a pre-filtering step. The top scoring pairs methodology was originally described in Geman et al. (2004) and the unique TSP idea was described in Tan et al. (2005).

Value

A tsp object with elements:

index	A two-column matrix where each row is a pair of indices from the data matrix achieving the top score
tspscore	The rank based score described in Geman et al. (2004), essentially the empirical average of sensitivity and specificity for the pair.
score	The tie-breaking score described in Tan et al. (2005).
grp	The binary group indicator.
tspdat	Row i and row (i + Number of total TSPs) of this data matrix represent the expression data for the ith TSP pair.
labels	The group labels for the two groups as defined by the grp variable.

Author(s)

Jeffrey T. Leek <jtleek@jhu.edu>

References

D. Geman, C. d'Avignon, D. Naiman and R. Winslow, "Classifying gene expression profiles from pairwise mRNA comparisons," *Statist. Appl. in Genetics and Molecular Biology*, 3, 2004.

A.C. Tan, D.Q. Naiman, L. Xu, R.L. Winslow, D. Geman, "Simple decision rules for classifying human cancers from gene expression profiles," *Bioinformatics*, 21: 3896-3904, 2005.

See Also

[tspplot](#), [ts.pair](#), [tspsig](#), [predict.tsp](#), [summary.tsp](#)

Examples

```
## Not run:
## Load data
data(tspdata)

## Run tspcalc() on a data matrix and grp vector
tsp1 <- tspcalc(dat,grp)
tsp1$index
```



```
## Run tspcalc() on an expression set and a column of the pData matrix
tsp2 <- tspcalc(eSet1,1)
tsp2$index
## End(Not run)
```

tspdata	<i>Simulated gene expression data in both matrix and expression set format.</i>
---------	---

Description

These data sets can be used to illustrate the TSP functions. The data consist of two simulated data sets "dat", "dat2", a group indicator "grp" for "dat", and two expression sets "eSet1" and "eSet2" where the expression of eSet1 is "dat", the expression of eSet2 is dat2, and the pData for eSet1 consists of "grp".

Usage

```
dat
```

tspplot	<i>Graphical display of tsp objects</i>
---------	---

Description

Graphical display of tsp objects

Usage

```
tspplot(tspobj)
```

Arguments

tspobj A tsp object.

Details

tspplot() creates a plot of each top scoring pair. The figure plots the expression for the first gene in the TSP pair versus the expression for the second gene in the TSP pair across arrays. The user defined groups are plotted in the colors red and blue. The score for the pair is shown across the top of each plot. If there is more than one TSP, hitting return will cycle from one TSP to the next.

Value

Nothing of interest.

Author(s)

Jeffrey T. Leek <jtleek@jhu.edu>

References

D. Geman, C. d'Avignon, D. Naiman and R. Winslow, "Classifying gene expression profiles from pairwise mRNA comparisons, *Statist. Appl. in Genetics and Molecular Biology*, 3, 2004.

See Also

[tspcalc](#), [ts.pair](#), [tspsig](#), [predict.tsp](#), [summary.tsp](#)

Examples

```
## Not run:
## Load data
data(tspdata)
tsp1 <- tspcalc(dat, grp)
tspplot(tsp1)

## End(Not run)
```

tspsig

Significance calculation for top scoring pairs

Description

This function calculates the significance of a top-scoring pair. It can be run after `tspcalc()` to calculate how strong a TSP is.

Usage

```
tspsig(dat, grp, B=50, seed=NULL)
```

Arguments

dat	Can take two values: (a) an m genes by n arrays matrix of expression data or (b) an eSet object
grp	Can take one of two values: (a) A group indicator in character or numeric form, (b) an integer indicating the column of <code>pData(dat)</code> to use as the group indicator
B	The number of permutations to perform in calculation of the p-value, default is 50.
seed	If this is a numeric argument, the seed will be set for reproducible p-values.

Details

`tspsig()` only works for two group classification. The computation time grows rapidly in the number of genes, so for large gene expression matrices one should be prepared to wait or do a pre-filtering step. A progress bar is shown which gives some indication of the time until the calculation is complete. The top scoring pairs methodology was originally described in Geman et al. (2004).

Value

p	A p-value for testing the null hypothesis that there is no TSP for the data set dat.
nullscores	The null TSP scores from the permutation test.

Author(s)

Jeffrey T. Leek <jtleek@jhu.edu>

References

D. Geman, C. d'Avignon, D. Naiman and R. Winslow, "Classifying gene expression profiles from pairwise mRNA comparisons," *Statist. Appl. in Genetics and Molecular Biology*, 3, 2004.

See Also

[tspplot](#), [ts.pair](#), [tspcalc](#), [predict.tsp](#), [summary.tsp](#)

Examples

```
## Not run:
## Load data
data(tspdata)

## Run tspcalc() on a data matrix and grp vector
tsp1 <- tspcalc(dat,grp)

## Run tspsig() to get a p-value
p <- tspsig(dat,grp)
p
## End(Not run)
```

Index

*Topic **datasets**

dat, 1
dat2, 1
eSet1, 2
eSet2, 2
grp, 2
tspdata, 9

*Topic **misc**

plot.tsp, 3
predict.tsp, 4
summary.tsp, 5
ts.pair, 6
tspcalc, 7
tspplot, 9
tspsig, 10

dat, 1
dat2, 1

eSet1, 2
eSet2, 2

grp, 2

plot.tsp, 3
predict (*predict.tsp*), 4
predict.tsp, 3, 4, 6–8, 10, 11

summary (*summary.tsp*), 5
summary.tsp, 3, 4, 5, 7, 8, 10, 11

ts.pair, 3, 4, 6, 6, 8, 10, 11
tspcalc, 3, 4, 6, 7, 7, 10, 11
tspdata, 9
tspplot, 3, 4, 6–8, 9, 11
tspsig, 3, 4, 6–8, 10, 10